

# Neerlandia Coop



Box 188  
Neerlandia AB  
T0G 1R0



## Sonic 2 Cycle Oil



### Description

Sonic Two-Cycle Oil is a quality 2-cycle oil that is recommended for both air cooled and older water cooled 2-cycle engines. It is formulated to meet the requirements of low ash applications. Although predominantly used in tank mix applications, it may be injected in specific equipment.

### Application

Sonic Two-Cycle Oil is recommended for use in 2-cycle engine requiring a fuel/oil ration of 50:1 or less and a NMMA low ash formulation. Sonic Two-Cycle Oil can be used in chain saws, lawn mowers, snow throwers and utility motors that require a 2-cycle engine oil. In all cases the manufacturer's recommendations should be consulted.

Note: Do not use this product in equipment that calls for a synthetic 2-cycle engine oil.

### Performance Features

Sonic Two-Cycle Oil provides the following performance features:

1. Prevents piston scuffing
2. Minimize ring sticking and spark plug fouling
3. Minimize rust, corrosion and exhaust system deposits
4. Eliminate pre-ignition
5. Pre-diluted for easier mixing at all temperatures
6. Qualified TC and low ash

## Availability

Sonic Two-Cycle Oil is available in 1 litre and 500 millilitre bottles (12 per case).

## Typical properties

Colour	Blue
Kinematic Viscosity @ 40°C, cst	37.1
Kinematic Viscosity @ 100°C, cst	6.6
Viscosity Index	134
Pour Point	-36°C

## Mixing Table\*

<b>Gasoline to Oil Ratio</b>	<b>Litres of Gasoline</b>				
	<b>5L</b>	<b>10L</b>	<b>15L</b>	<b>20L</b>	<b>25L</b>
16:1	300mL	600mL	900mL	1.2L	1.5L
25:1	200mL	400mL	600mL	800mL	1.0L
32:1	150mL	300mL	450mL	600mL	750mL
40:1	125mL	250mL	375mL	500mL	625mL

\*The body of the table shows the amount of oil that must be added to obtain the gasoline to oil ration (1 litre = 1000 mL)