

# Neerlandia Coop



Box 188  
Neerlandia AB  
T0G 1R0



## ATF SL



### Description

Sonic ATF SL is an automatic transmission fluid that can be used as a top-off or service fill when Dexron III / Mercon, Mercon V, Chrysler ATF+3, ATF+4, or Allison C-4 (Synthetic) is called for.

Sonic ATF SL can be used in other on or off-road applications as a hydraulic fluid, powershift fluid, and power steering fluid.

### Application

Sonic ATF SL meets the performance requirements of;

- Dexron III / Mercon.
- Mercon V.
- Chrysler ATF+3 or ATF+4.
- Allison C-4 (Synthetic) & TES295.
- Voith specifications.
- ZF.
- Caterpillar TO-2.
- Hagglands-Dennison HF-O.
- Vickers 35VQ25A.

### Performance Features

Sonic ATF SL provides the following performance features:

- 1.-Full Synthetic Formulation
  - Exceptional low temperature fluidity
  - Oxidation stability
  - Reduces varnish build-up

2. - Improved high temperature operation
  - Improved fuel mileage
  - Extended transmission life
  - Protects against fluid breakdown
3. Corrosion Protection
  - Protects all metal components
  - Reduces sludge deposits
  - Maintains lubricity under severe operating conditions
4. Unsurpassed Performance
  - Performance surpasses expectations
  - Excellent shift feel
  - No transmission shudder
  - Operates smoothly
  - Protects transmission gears

#### Availability

Sonic ATF SL is available in 205 litre drums and 1 litre bottles (12 per case).

#### Typical Properties

<b>Colour</b>	<b>Red</b>
<b>Viscosity @ 40°C</b>	<b>38.11</b>
<b>Viscosity @ 100°C</b>	<b>7.75</b>
<b>Viscosity Index</b>	<b>179</b>
<b>Pour Point</b>	<b>-63°C</b>