

Neerlandia Coop



Box 188
Neerlandia AB
T0G 1R0



Chain Oil



Description

Sonic Chain Oil is blended to produce a tacky product that will adhere to the guide bar and chain of power saws.

Application

Recommended for use in the chain oil reservoir of the majority of chain saws to protect the guide bar and chain from excessive wear. It can also be used as a chain lubricant for chains that require hand oiling.

Performance Features

Sonic Chain Oil provides the following features:

1. Has a tackiness agent enabling the oil to maintain a protective oil film to lubricate the chain and bar
2. Has anti-wear additives to protect against wear of the metal parts
3. Anti-rust protection
4. Provides good flowability at all temperatures with the appropriate weight

Availability

Sonic Chain Oil is available in three weights; Light, Medium and Heavy. Light and Heavy are available in 20 litre pails and 4 litre jugs (4 per case). Medium is only available in 1 litre bottles (12 per case).

Typical Properties

	Light	Medium	Heavy
Weight			
Color	Red	Red	Red
API Gravity	29.0	28.0	27.0
Kinematic Viscosity @ 40°C, cst	53.2	100.0	156.8
Kinematic Viscosity @ 100°C, cst	8.7	11.0	16.9
Viscosity Index	135	95	95
Pour Point	-37°C	-20°C	-15°C