

Neerlandia Coop



Box 188
Neerlandia AB
T0G 1R0



Sonic Dynamix Plus



Description

Sonic Dynamix Plus is a premium quality, ashless, universal, two-cycle motor oil. It is certified by NMMA as a TC-W3, and CDG as a Grade 4 fluidity/miscibility. It is approved for use in a Tank Mix or Oil Injection engines. TC-W3 supersedes TC, TC-W and TC-W II performance requirements.

Performance Features

Sonic Dynamix Plus provides superior performance in the areas of:

1. Improved full throttle performance
2. Extended engine life
3. Reduced engine deposits
4. Reduced engine fouling, under severe operating conditions
5. Improved light throttle operation

Applications

Sonic Dynamix Plus is recommended for use in two-cycle outboard, snowmobile, motorcycle or golf cart that:

1. Require a TC-W, TC-W II or TC-W3 qualified product
2. Require low ash or no ash formulations
3. Require a Tank Mix up to and including 100:1 ratio as recommended by the engine manufacturer
4. Oil injected engines
5. Most water-cooled and some air-cooled applications

6. Require a low temperature performance as required in API class 4 performance tests
7. Meets or exceeds original equipment performance requirements

Note: Do not use in orbital or Ficht designed engines.

Availability

Sonic Dynamix Plus is available in 110 litre drums, 20 litre pails, 5 litre jugs (4 per case), 1 litre and 500 millilitre bottles (12 per case).

Typical Properties

Colour	Blue
Kinematic Viscosity @ 40°C, cSt	24.9
Kinematic Viscosity @ 10°C, cSt	5.14
Viscosity Index	141
Pour Point	-45°C
Flash Point	72°C