


# Neerlandia Coop



Box 188  
Neerlandia AB  
T0G 1R0



## Industrial Hydraulic Oil SL



### Description

Industrial Hydraulic All Weather SL is a multi-viscosity, premium quality, partial synthetic industrial lubricant for a wide range of applications.

### Application

Industrial Hydraulic All Weather SL is recommended for use in a wide variety of hydraulic systems. It meets the requirements of Denison HF-0, Denison HF-2, Cincinnati Milacron P-68, P-69, P-70 and CGSB-36Md. It can be used in Vicker's vane pumps (Qualified Vickers 35VQ25, I286-S, M2950-S) and either pump applications.

Industrial Hydraulic All Weather SL can be used in air compressors, gear boxes, and any other applications requiring a machine tool oil.

Industrial Hydraulic All Weather SL is fluid through a wide range of ambient temperatures. It operates from -54°C to 40°C, with a film thickness equivalent to an ISO 32.

### Performance Features

Sonic Industrial-Hydraulic All Weather SL has the following features:

1. Contains excellent oxidation inhibitors to protect against oxidation degradation caused by high temperature or aging.
2. Rust inhibitors to protect against corrosion during conditions of high moisture.
3. Anti-wear additives to prevent wear of hydraulic components during use.

4. Anti-Foaming agents to insure good lubrication and a positive response in hydraulic systems.
5. The fluid has good thermal stability.

### Availability

Sonic Industrial Hydraulic All Weather SL is available in 205 litre & 110 litre drums and 20 litre pails.

### Typical Properties

<b>ISO Grade</b>	<b>32</b>
Viscosity @ 40°C, cst	32.7
Viscosity @ 100°C, cst	6.6
Viscosity Index	161
Pour Point	-54°C