

Neerlandia Coop



Box 188
Neerlandia AB
T0G 1R0



Sonic Moly Guard SL



Description

Sonic Moly Guard SL offers superior performance and pumpability in both high and low temperature applications. It offers excellent year around performance in automotive, industrial and farm applications. Due to it's synthetic component, it can be used in most applications where an NLGI grade 1 or 2 is required and is compatible with most other greases. SONIC Moly Guard SL contains 3% Molybdenum Disulphide (Moly) and is recommended for applications requiring a Moly product.

Application

Sonic Moly Guard SL meets manufacturer's requirements pertaining to:

- Wheel Bearings
- Universal Joints
- Various Industrial Applications
- Ball Joints
- Electric Motors
- Multi-purpose applications where a standardized product is required
- Clutch Throwout Bearings
- Chassis Fittings
- Severe Conditions
- Applications requiring up to 3% Moly

Performance Features

1. Extends lubrication intervals and reduces down-time
2. Excellent rust and corrosion protection
3. Resists water wash-out
4. High heat resistance with a typical +290°C/500°F dropping point
5. Meets EP (extreme pressure) requirements to reduce wear
6. Superior low temperature pumpability to -40°C and superior performance to -50°C
7. Outstanding Oxidation resistance
8. Approved for applications where 3% Moly is required
9. Meets or exceeds NLGI - GC-LB performance requirements
10. Operating range between -40°C and +260°C

Availability

Sonic Moly Guard is available in 55 kilogram kegs and 400 gram cartridges (10 per box, 4 boxes per case).

Typical Properties

Dropping Point	260°C min.
Penetration (ASTM D 217)	295-315
Timkin OK Load	65
4-Ball Weld	500KgF
4-Ball LWI	40
Colour	Black
Stability	+20
NLGI Grade	1.5
NLGI Performance	GC-LB
Rust Prevention	Pass
Texture	Buttery/Tacky