

Neerlandia Coop



Box 188
Neerlandia AB
T0G 1R0



MP Gear Oil SL



Description

Sonic MP Gear Oil SL is a synthetic based, heavy duty gear lubricant that is blended for year around applications (including sub-zero conditions). Sonic MP Gear Oil SL SAE 50 is a severe service manual transmission fluid capable of extending drain intervals to 500,000 miles.

Application

Sonic MP Gear Oil SL is recommended for use in transmission, differentials, or industrial applications where extreme heat or cold is a concern. This includes many heavy trucking, extended drain or extended warranty applications.

Performance Features

Sonic MP Gear Oil SL provides superior performance in the areas of:

1. Exceptional extreme pressure gear protection.
2. Extended rust and corrosion protection.
3. Superior shear stability even under high temperature conditions.
4. Improved fuel economy.
5. Superior cold weather performance.
6. Compatible with most seals used today.
7. Meets the performance of EATON PS-164 (Rev 7) extended drains service.

Warranty Approvals

Sonic MP Gear Oil SL is approved for:

1. 0-76Q and 0-76E
2. DANA SHAES - 234
3. DANA SHAES - 256 REVC
4. ArvinMeritor 0-76N, 0-76E
5. Mack GO-J Plus
6. API GL-5 and mT-1
7. MIL-PRF-2105E, MIL-L-2105D
8. International TMS 6816
9. SAE J2360
10. Approved for transfer cases and wheel ends

Availability

Sonic MP Gear Oil SL is available in 60 litre kegs, 20 litre pails and 5 litre jugs (4 per case). Not all grades are available in all container sizes.

Typical Properties

SAE Grade	75W90	80W140	SAE 50
Kinematic Viscosity @ 40°C	122	240	125
Kinematic Viscosity @ 100°C	16.7	28.0	18.0
Viscosity Index	147	151	163
Pour Point	<-45°C	<-40°C	<-40°C