

Neerlandia Coop



Box 188

Neerlandia AB

TOG 1R0



Sonic Silver Motor Oil



Description

Sonic Silver Motor Oil is a high quality multi-grade motor oil for use in today's gasoline engines. Sonic Silver Motor Oil is friction modified to provide added fuel economy by reducing friction between moving parts.

Application

Sonic Silver Motor Oil is fully approved for API services SM, SL, SJ, and ILSAC GF-4. It is energy conserving, which is required for new car warranty gasoline engines. Sonic Silver Motor Oil is a quality motor oil that offers good oxidation and sheer stability.

Performance Features

1. Excellent detergent and dispersancy to ensure engine cleanliness and long engine life
2. Contains anti-wear and rust / corrosion inhibitors to protect vital moving parts
3. Increased oxidation stability to prevent oil thickening
4. Friction modified to provide added fuel economy
5. Fully approved for the latest new car warranties
6. Approved for GF-4 (except 10W40)
7. Compatible with modern catalytic converters
8. Sonic Silver 10W40 is specifically formulated to function as an engine oil or a transmission oil in motor cycle applications

Availability

Sonic Silver Motor Oil is available in 205 litre drums, 4 litre jugs (4 per case) and 1 litre bottles (12 per case).

Typical Properties

SAE Grade	5W20	5W30	10W30	10W40
Viscosity @ 40°C, cst	48	67	69	105
Viscosity @ 100°C, cst	8.5	11.0	10.5	15.2
Viscosity Index	162	160	140	152
Cold Crank Viscosity (Cp @ °C)	3,440/-30	5,350/-30	5,960/-25	6,380/-25
Pumping Viscosity (Cp @ °C)	9,368/-35	18,062/-35	23,047/-30	35,680/-30
Sulphated Ash (% wt.)	1.04	1.02	1.05	0.8
Pour Point	-45°C	-40°C	-40°C	-39°C
Flash Point	222°C	228°C	195°C	205°C