

Neerlandia Coop



Box 188
Neerlandia AB
T0G 1R0



Sonic XL-S 2 Cycle Oil



Description

Sonic XL-S is an advanced synthetic blend, low-ash, two-cycle engine oil. It is precisely blended to offer superior performance in severe or high performance applications. Including unique designs like ORBITAL and FITCH engines. This oil meets or exceeds the warranty requirements of original engine manufacturers requiring low ash engine oil.

Sonic XL-S has Zyvec. Zyvec is an additive that extends engine life by reducing piston scuffing, improves fuel system and combustion chamber cleanliness, protects against ring sticking, and improves high temperature oil film performance. It is capable of doubling engine life.

Application

Sonic XL-S is specifically blended for injection applications, but can also be used in tank mix applications up to 100:1 (as specified by the OEM). This oil is suitable for use in both EFI (electronic fuel injection) and DFI (direct fuel injection) engines. It is recommended for the following two stroke applications:

- Snowmobiles (including racing applications)
- Personal watercraft
- Hi-impact chainsaws
- Motocross motorcycles
- All terrain vehicles
- Lawn movers, string trimmer, and other garden equipment

Performance Features

- Low smoke
- Emissions reductions
- Anti-scuff performance
- Ring stick protection
- Improved engine cleanliness
- Corrosion protection
- Increased engine life
- Superior low temperature performance
- Compatible with fuels containing alcohol

Availability

Sonic XL-S is available in 4 litre bottles (4 per case) and 1 litre bottles (12 per case).

Typical Properties

Colour	Orange
Kinematic Viscosity @ 40° C, cst.	31.0
Kinematic Viscosity @ 100° C, cst.	6.5
Viscosity Index	166
Pour Point	-63°C